

INDOOR/OUTDOOR 10-WATT SPEAKER

**MPI-35
MPI-35F**

SPECIFICATIONS

moose

APPLICATION

Ease in mounting and good looks are just two of the reasons that make the MPI-35 and Flush-Mount MPI-35F popular. The MPI-35 has a removable back plate which attaches easily to any flat surface. The MPI-35F mounts semi-flush into a hollow surface with a snap-on trim ring to conceal the mounting screws. Both are rated for operation at 10 Watts nominal, 15 Watt Peak.

SPECIFICATIONS


- ☐ Maximum Input: 10 Watts Nominal, 15 Watts Peak
- ☐ Voice Coil Impedance: 8 Ohms
- ☐ Dimensions: MPI-35 Depth - 2.20 inches
 Width - 4.33 inches
 MPI-35F Depth - 1.50 inches
 Width - 6.25 inches
 Height - 5.00 inches
- ☐ Color: Bone White
- ☐ Mounting: MPI-35 Surface Mount With Removable Back Plate
 MPI-35F Mounts Semi-Flush Into A 3.5 x 1.5 Inch Deep Hole. A Snap-on Trim Ring Conceals The Mounting Screws.
- ☐ Housing: Impact Resistant Molded Plastic
- ☐ Weight: 2 lbs
- ☐ Frequency Response: 700 to 8,000 Hz.
- ☐ Connections: 2 Conductor Cable - 8" (Minimum) Length.

FEATURES

- ☐ Heavy Duty, High Quality Magnet
- ☐ Strong, Durable Mylar Diaphragm
- ☐ Compact Size
- ☐ Surface (35) or Semi-flush (35F) Mounting
- ☐ Concealed Wall Mounting Hardware (Included)

The MPI-35/MPI-35F are suitable for multiple speaker use with an MPI-11, JDS-100, JDS-102, or JDS-108 siren driver. However, their 15 watt rating is insufficient for direct single connection since the output of these drivers is 20 to 30 watts. If not connected in series with another speaker, a 5 Ohm - 10 watt resistor should be added in series to limit the excess current from damaging the MPI-35/MPI-35F. These resistors (Part No. MPI510) can be obtained from your local distributor.

MPI-35



MPI-35F

